

CI/SFB	(47)	Vv1	April 2014
Uniclass		JJ31: L52	
Issue 01			



# Enviroflex™ Wearcoat Clear

## Liquid Applied Roof Waterproofing Systems

### Introduction

Designed to provide the optimum combination of aesthetic and functional performance Enviroflex™ anti-skid surfacing products form an integral part of a complete system where waterproofing and surfacing are required.

Enviroflex™ surfacing products can be applied onto Enviroflex™ waterproofing membrane to form a durable, hard wearing surface, ideal where access for maintenance is required.

### Description

Enviroflex™ Wearcoat Clear is a single component, low solvent coating based on a light-stable resin. It is translucent in colour and is supplied in various container sizes.

### Intended Use

Enviroflex™ Wearcoat Clear forms part of the Enviroflex™ Walkway System and is used as a final encapsulation and UV protection layer above the embedded Enviroflex™ Quartz.

### Application

Apply the Enviroflex™ Wearcoat Clear liquid in two coats.

For ease of application, transfer the Enviroflex™ Wearcoat Clear to a large decorator's roller tray before applying with a roller.

Avoid pouring the Enviroflex™ Wearcoat Clear directly from the tin onto the walkway surface.

Personal Protective Equipment should be worn.

### Usage Rate

Enviroflex™ Wearcoat Clear should be applied in two coats at a combined coverage rate of approximately 0.5 L/m<sup>2</sup>.

### Properties

Container Size	3.8 L; 7.5 L; 20L
Form	Liquid
Colour	Translucent
Application Rate	Approx 0.5 L·m <sup>-2</sup>
Coverage per Container	3.8 L : Approx 7.6 m <sup>2</sup> 7.5 L : Approx 15 m <sup>2</sup> 20 L : Approx 40 m <sup>2</sup>
Rainproof after	Approx 1 hour <sub>1</sub>
Can be walked on after	Approx 2 hours <sub>1</sub>
Shelf Life	12 months

1. Dependant on environmental conditions. Values attained at 23 °C and 50% rel humidity. Times given are reduced with higher (and increased with lower) surrounding and work surface temperatures.

### Quality Assurance

Enviroflex™ products are supplied under a Quality Management System approved to ISO 9001:2000 by BSI Quality Assurance.



QMS: Q5556

### Storage

Store the product in a dry and cool environment.

### Disposal

Components (Liquid)	EWC	08 04 09
Components (Cured)	EWC	08 04 10

### Technical Services

Specialist advice and design guidance on all matters relating to Enviroflex™ systems is freely available from our Technical Department at the address below.

### Availability

Description	Size
Enviroflex™ Wearcoat Clear	3.8 L
Enviroflex™ Wearcoat Clear	7.5 L
Enviroflex™ Wearcoat Clear	20 L

NOTE: This information is given in good faith being based on the latest knowledge known to Icopal Limited. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume; based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.