

CI/SFB	February 2017
(47)	Vw1
Uniclass JJ31 : L52	
Issue 01	

Sealoflex® Rust X-2020

Liquid Applied Roof Waterproofing Systems

Description

Sealoflex® Rust X-2020 is a thin liquid polymer which transforms iron oxide into a stable and insoluble metallo-organic compound. Rust X-2020 creates a sound base for the application Sealoflex® Metal Etch Primer.

Intended Use

Sealoflex® Rust X-2020 is applied to surfaces where residual rust cannot be removed and on areas of light rust, prior to application of the Sealoflex® Metal Etch Primer.

Advantages


- Free of organic solvents
- Readily penetrates
- Chloride free
- Neutralizes rust action
- Creates a ready to prime, rust free surface
- Safe to handle, store and transport

Surface Preparation

Remove oil or grease before application. Remove loose rust and mill scale by wire brush, abrasive disk or sand paper. In heavy industrial or marine environments, rust always contains salts which must be washed down with clean water before treatment with Sealoflex® Rust X-2020.



During application.



Before and After Rust X-2020.

Properties

Container Size	3.78 litres
Form	Liquid
Colour	Milky White (dries blue-black)
Density	1.0065 kg/litre
Coverage Rate per tin	38 m ²
Application Temperature	5 °C to 40 °C
Application Rate	Approx 0.1 litres per m ²

Application

Sealoflex® Rust X-2020 is ready for use after stirring. A single application without excess is sufficient. Use a stiff brush to enhance penetration, although application by low pressure sprayer or roller is acceptable. Sealoflex® Rust X-2020 must be allowed to cure for at least 3 hours before priming.

NOTE: Sealoflex® Rust X-2020 is not a “stand alone” paint or primer. It must be coated with Sealoflex® Metal Etch Primer within 48 hours.

Precautions: Protect adjacent surfaces such as concrete to prevent staining.

Personal Protective Equipment should be worn.

Cleaning

Wash tools and equipment with water.

Storage

Keep containers tightly closed when not in use. Storage temperatures must be between 5 °C and 40 °C.

Do not allow to freeze.

In original unopened containers, the shelf life is 12 months.

Availability

Item Code	Description	Size
3101718	Sealoflex® Rust X-2020	3.78 L

NOTE: This information is given in good faith being based on the latest knowledge known to Icopal Limited. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer’s instructions have not been followed. The user should not assume; based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.