

CI/SFB	February 2017
(47)	Vv1
Uniclass JJ31 : L52	
Issue 01	

Sealoflex® Metal Etch Primer

Liquid Applied Roof Waterproofing Systems

Description

Sealoflex® Metal Etch Primer is a water-based acrylic primer for optimum corrosion protection of ferrous metal surfaces.

Intended Use

Sealoflex® Metal Etch Primer is used on bare ferrous metal as an adhesion coat prior to the application of the specified Enviroflex® or Elastoflex® Ultima liquid waterproofing system.

Advantages

- Forms a tough, non-chip film
- Good chemical and abrasion resistance
- Quick drying
- Inhibits rust formation
- No dangerous fumes from solvents
- Used as a primer for all bare metal accessories, eg drip edge trims, etc.
- Excellent adhesion to PDVF and silicone polyester based coatings

Surface Preparation

Surface must be clean, oil and grease free and free of loosely adhering particles. Remove loose rust and mill scale by wire brush, abrasive disk or sand paper. Rusted areas should then be coated with Sealoflex® Rust X-2020 prior to application of Sealoflex® Metal Etch Primer.



Properties

Container Size	3.78 litres
Form	Liquid
Colour	Oxide red
Density	1.198 kg/litre
Application Temperature	5 °C and 30 °C
Coverage Rate per tin	19 m ²
Application Rate	Approx 0.2 litres per m ²

Application

Sealoflex® Metal Etch Primer is ready for use after stirring. Apply Sealoflex® Metal Etch Primer by brush, roller or spray. Allow to dry. Once dry, coat with the appropriate waterproof coating system.

Do not apply Sealoflex® Metal Etch Primer over existing asphalt, bituminous coatings or bituminous aluminium coatings.

Personal Protective Equipment should be worn.

Cleaning

Wash tools and equipment with water immediately after use. Cured Sealoflex® Metal Etch Primer can be removed with mineral spirits.

Storage

Keep containers tightly closed when not in use. Storage temperatures must be between 5 °C and 30 °C.

Do not allow to freeze.

In original unopened containers, the shelf life is 12 months.

Availability

Item Code	Description	Size
3101717	Sealoflex® Metal Etch Primer	3.78 L

NOTE: This information is given in good faith being based on the latest knowledge known to Icopal Limited. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume, based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.