

Roofgard Parapet Outlet

**Anderson
Monarflex**



CI/StB July 2006
| (13.9) | Ln6 | L2 |

**High performance
stainless steel
parapet outlets
designed to ensure
the waterproofing
integrity of the roof
remains intact.**



**One of a range of Roofgard accessories specially designed
to meet the exacting standards of modern flat roofing**

Roofgard Parapet Outlets



**1 Lead chute 2 Extension 3 Steel Chute
4 Parapet Outlet 5 Parapet Outlet Grate**

The Anderson Monarflex Roofgard Parapet Outlet is manufactured from the highest quality stainless steel, incorporating a polymer modified polyester reinforced membrane flange for extra durability.

The Roofgard parapet outlet is designed as a stainless steel square to round spigot. A round section enables a watertight seal to be achieved to the rainwater pipework. If the Roofgard parapet outlet is to be fixed to pipework less than 110mm diameter a proprietary reducer must be used. The spigot can also be fitted to our range of parapet outlet attachments. The Parapet Outlet attachments have internal "O" ring seals for watertight connection.

Parapet Outlet Attachments

The Parapet Outlet attachments are to be used in conjunction with Parapet Outlets. There are two forms of Parapet Outlet attachments, either a Chute or an Extension.

Chute Attachments

The Chute attachments are normally used to discharge water to a hopper head at the top of a down pipe. Two types of chutes are available.

■ Lead Chute

The Lead Chute consists of a steel round to square section, finished with a lead spout. This attachment would be used when the external facade requires aesthetic consistency and a high aesthetic value.

Diameter: 110mm - 100 x 100mm with lead

Pipe Length: 170mm

Chute Length: 110mm

■ Steel Chute

The Steel Chute consists of a steel round to square section with a self-finished spout. The square section is profiled to form the spout and would be used as an economic alternative.

Diameter: 110mm - 100 x 100mm, cut 45°

Chute Length: 190mm

■ Extension Attachment

The extension attachment consists of a steel round to round section, which extends the normal spigot length by 220mm. This attachment would be used when draining through a particularly thick parapet wall.

Diameter: 110mm

Length: 300mm

■ Parapet Outlet Grate

The Parapet Outlet Grate is a specially designed angled stainless steel perforated leaf guard. It is fixed in to the Parapet Outlet via an sprung 'A' clamp that locates the fixing spigots internally.

Roofgard Accessories Range

A range of accessories specially designed to meet the exacting standards of modern flat roofing whilst maintaining the waterproofing integrity of the roof. Range includes:

- **Roofgard Cable & Pipe Duct**
- **Roofgard AnchorFast Lightning Conductor Clip**
- **Roofgard Cowled Telescopic Vent**
- **Roofgard Roof Outlet**
- **Roofgard GRP Trim**
- **Roofgard Plant & Equipment Support System**

Icopal Ltd

Barton Dock Road
Stretford, Manchester
M32 0YL
Telephone: 0161 865 4444
Fax: 0161 866 9859
Technical Fax: 0161 865 8433
email: marketing.uk@icopal.com

Northern Ireland

Telephone: 028 9037 0888
Fax: 028 9037 0747

Republic of Ireland

Telephone: 1800 409 056
Fax: 1800 409 055

Technical Support

To assist specifiers and contractors, Icopal offers FREE technical support and advice on all aspects of waterproofing. Our service includes the provision of detailed CAD drawings, complete system specifications and a telephone advice line.

For further information call

0161 865 4444

or visit

www.icopal.co.uk