



CI/SFB	(47)	Xn6	July 2014
Uniclass	P7110		
Issue 02			

# Roofgard Adjustable Paving Support

## Adjustable Support System for Paved/Terrace Areas

The Roofgard Paving Support System provides a versatile cost effective means of creating a fully supported and stable raised paved area, terrace, walkway or balcony.

- Support head interchangeable with three varying bases and additional extension collars to provide variable paving heights from 40mm to 225mm.
- Corrosion and maintenance-free
- High resistance to deformation

TECHNICAL DETAILS	
Material	Polypropylene
Colour	Black
Height range	40 – 225 mm
Short Unit:	40 – 65 mm
Medium Unit:	60 – 105 mm
Tall Unit:	100 – 145 mm
Extension Collar:	40 mm
Base Diameter	330 cm <sup>2</sup>
Load per unit	>1000 kg
Biological / Chemical resistance	Unaffected by moulds and algae and good resistance to alkali
Service Temperature	-20 °C to 65 °C
<b>Roofgard Paving Cushion</b>	
Material	Elastomeric pad
Availability	2 types; to suit concrete or timber tile
Noise Reduction	Approx 2 dB
<b>Roofgard Support Plate</b>	
Material	Polypropylene
Dimensions/mm (l.w.h)	400 x 140 x 29
<b>Roofgard Drainage Grate</b>	
Material	Galvanised Steel
Colour	Ivory
Dimensions/mm (l.w.h)	500 x 100 x 50

NOTE: This information is given in good faith being based on the latest knowledge known to Icopal Limited. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume; based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.