



Parabit Solo Reinforcing Grid

TECHNICAL DATA SHEET

Material	Resin coated interwoven glass fibre reinforcement
Colour	Blue
Packaging	Supplied as individually wrapped rolls
Roll Size	50 x 1m
Product code	3100537

Characteristic	Test method	Typical Value	MLV/Range	Units
Weight	-	-	110	g/m ²
Mesh size	-	-	11.5 x 10	mm
Composition	glass fibre	-	85	%
	resin	-	15	
Yarn count	warp	-	8.0	Threads / 10cm
	weft	-	7.0	
Tensile strength at break	warp	-	1.500	N/50mm
	weft	-	1.400	
Elongation at break	warp	-	3.3	%
	weft	-	3.6	

Description of product

Parabit Hot Melt is a seamless reinforced hot liquid applied modified bitumen waterproofing system.

Type of application

Parabit Hot Melt is used as a reinforced self-healing waterproofing membrane specially developed for use in inverted, green and plaza deck roof situations. Designed for concrete substrates, Parabit Hot Melt represents the optimum solution for speed of application and cost effectiveness. Membranes should be installed in accordance with manufacturer's guidelines.

Storage & Transportation

Parabit Solo Reinforcing Grid is delivered in individually wrapped rolls and should be stored internally or under a protective cover to provide protection from direct rain and physical damage.

NOTE: This information is given in good faith being based on the latest knowledge known to Icopal Limited. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice.