



# Parabit Duo Reinforcing Fabric

## TECHNICAL DATA SHEET

Material	Spunlaid non-woven polyester reinforcement
Colour	White
Packaging	Supplied as individually wrapped rolls
Roll Size	100 x 1m
Product code	3101604

Characteristic	Test method	Typical Value	MLV/Range	Units	
Weight	EN 29073-1	-	50	g/m <sup>2</sup>	
Thickness	EN 29073-2	-	0.4	mm	
Tensile strength at break	Machine Direction	EN 29073-3	-	155	N/50mm
	Cross Direction	EN 29073-3	-	125	
Elongation at break	Machine Direction	EN 29073-3	-	22	%
	Cross Direction	EN 29073-3	-	23	

### Description of product

Parabit Hot Melt is a seamless reinforced hot liquid applied modified bitumen waterproofing system.

### Type of application

Parabit Hot Melt is used as a reinforced self-healing waterproofing membrane specially developed for use in inverted, green and plaza deck roof situations. Designed for concrete substrates, Parabit Hot Melt represents the optimum solution for speed of application and cost effectiveness. Membranes should be installed in accordance with manufacturer's guidelines.

### Storage & Transportation

Parabit Duo Reinforcing Fabric is delivered in individually wrapped rolls and should be stored internally or under a protective cover to provide protection from direct rain and physical damage.

NOTE: This information is given in good faith being based on the latest knowledge known to Icopal Limited. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice.