

Sealoflex Endura Catalyst Powder

PRODUCT DATA

Container size	Bag:	0.10 kg or 1 kg
	Box:	25 kg
Form	Powder	
Colour	White	

DESCRIPTION

Sealoflex Endura Catalyst Powder is a powdered hardener for all Sealoflex Endura products.

INSTRUCTIONS FOR USE

Refer to the relevant Sealoflex Endura product data sheets for specific measuring, mixing and consumption information. Ensure catalyst is fully dissolved in resin before application.

STORAGE

Store Sealoflex Endura Catalyst Powder in a closed container and in a dry place away from ignition and heat sources at temperatures below +30 °C. Protect from direct sunlight.

This product may ignite spontaneously if exposed to excessive heat.

If Sealoflex Endura Catalyst Powder is stored at high temperatures, clumps will form in the free flowing powder and it will be unusable. Protect from contamination – even slight contamination from dirt, ash, rust, metal dust and the like can cause the rapid decomposition of the catalyst, creating a hazard and reducing its reactivity.

HEALTH & SAFETY

Information regarding transportation, handling, storage and disposal can be found on the Safety Data Sheet and on the label of the container. All recommendations and warnings must be observed.

TECHNICAL SERVICES

Specialist advice and design guidance on all matters relating to the Sealoflex Endura System is freely available from our Technical Services Team.

We are committed to continuously enhancing and improving our product range. We reserve the right to change our product specifications. We reserve the right to correct any typographical or clerical error or omission. For the latest information contact customer service.



BMI UK & Ireland
BMI House
2 Pitfield, Kiln Farm
Milton Keynes MK11 3LW
+44 (0) 1908 015760

bmigroup.com/uk