

Sealoflex Endura Cleaner

PRODUCT DATA

| | |
|-------------------------|-------------------------------------|
| Container size | 9 litres |
| Form | Liquid |
| Consumption rate | Allow 0.2 litres per m ² |
| Shelf life | 12 months (unopened) |
| Colour | Transparent |

INTENDED USE

Sealoflex Endura Cleaner is used to re-activate cured PMMA surfaces if work is interrupted; to degrease metal; and to clean tools..

DESCRIPTION

Sealoflex Endura Cleaner is a solvent-based universal cleaning agent.

INSTRUCTIONS FOR USE

Clean tools with Sealoflex Endura Cleaner immediately after use. Merely placing tools in the cleaner will not prevent hardening.

If Sealoflex Endura waterproofing and coating work is interrupted for more than 12 hours, the transition must be moistened with Sealoflex Endura Cleaner.

In the case of overcoating, the cleaner must be aired for approximately 20 to 25 minutes.

CONSUMPTION RATE

Depending on the degree of soiling and the type of substrate, allow a consumption rate of at least 0.2 L/m².

STORAGE

Can be stored unopened for approximately 12 months in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site.

HEALTH & SAFETY

Information regarding transportation, handling, storage and disposal can be found on the Safety Data Sheet and on the label of the container. All recommendations and warnings must be observed.

TECHNICAL SERVICES

Specialist advice and design guidance on all matters relating to Sealoflex Endura systems is freely available from our Technical Support Team.

We are committed to continuously enhancing and improving our product range. We reserve the right to change our product specifications. We reserve the right to correct any typographical or clerical error or omission. For the latest information contact customer service.



BMI UK & Ireland
BMI House
2 Pitfield, Kiln Farm
Milton Keynes MK11 3LW
+44 (0) 1908 015760

bmigroup.com/uk