

Sealoflex Prima UV Clear

Designed to provide the optimum combination of aesthetic and functional performance, Sealoflex Prima anti-skid surfacing products form an integral part of a complete system where waterproofing and surfacing are required.

PRODUCT DATA

Container size	10 kg
Form	Liquid
Application rate	Approx. 250 g per m ²
Coverage per pack	Approx. 40 m ²
Workability period	25 minutes*
Rainproof	Approx. 3 hours*
Walkable	Approx. 12 hours*
Shelf life	12 months
Colour	Translucent

* Dependent on environmental conditions. Values attained at 23 °C and 50% relative humidity. Times given are reduced with higher (and increased with lower) surrounding and work surface temperatures.

PRODUCT TESTING

BMI Sealoflex Prima has been independently site and laboratory tested by the British Board of Agrément and awarded BBA certificate number 13/5028.



INTRODUCTION

Sealoflex Prima surfacing products can be applied on to Sealoflex Prima waterproofing systems, or on to various new or existing substrates, to form a durable hard wearing surface for walkways.

DESCRIPTION

Sealoflex Prima UV Clear is a one component, low solvent coating based on a light-stable polyurethane resin. It is translucent in colour and is supplied in a 10 kg container.

INTENDED USE

Sealoflex Prima UV Clear forms part of the Sealoflex Prima Walkway System and is used as a final encapsulation and UV protection layer above the embedded Sealoflex Prima Quartz.

APPLICATION CONDITIONS

Apply only when atmospheric and substrate temperatures are greater than 5 °C. The surface of the substrate should be clean and dry and must be 3 °C above the dew point. If the surface is below or at dew point temperature then moisture can form at the surface and affect coating adhesion and curing.

APPLICATION METHOD

Apply the Sealoflex Prima UV Clear with a perlon fleece roller and always make a final pass using a dry roller to help create an even finish.

For ease of application, transfer the Sealoflex Prima UV Clear to a large decorator's roller tray. Avoid pouring the Sealoflex Prima UV Clear directly from the tin on to the walkway surface.

Walk-on time for the Sealoflex Prima UV Clear is approximately 12 hours depending on coverage rate used and ambient conditions. Allow to fully cure before trafficking.

Personal Protective Equipment (PPE) should be worn.

QUALITY ASSURANCE

Sealoflex Prima products are supplied under a Quality Management System approved to EN ISO 9001: 2015 by TÜV NORD CERT GmbH



STORAGE

Containers should be stored in a dry and cool environment on a flat, level, and clean surface away from sources of ignition, including pilot lights and sparks. Protect the product against moisture, direct sunlight and extremes of temperature.

Keep containers tightly closed when not in use. In original unopened containers the shelf life is 12 months.

DISPOSAL

Components A + B (Liquid)	EWC	08 04 09
Components A + B (Cured)	EWC	08 04 10

HEALTH & SAFETY

Health & Safety information supplied by manufacturer must be observed. Do not allow into the sewer system or ground.

TECHNICAL SERVICES

Specialist advice and design guidance on all matters relating to Sealoflex Prima systems is freely available from our Technical Services Team.

BMI UK & Ireland

BMI House
2 Pitfield
Kiln Farm
Milton Keynes
MK11 3LW
+44 (0) 1908 015760

We are committed to continuously enhancing and improving our product range. We reserve the right to change our product specifications. We reserve the right to correct any typographical or clerical error or omission. For the latest information contact customer service.