

Sealoflex Ultima Metal Etch Primer

Sealoflex Ultima Metal Etch Primer is a water-based acrylic primer. It is a component of the Sealoflex Ultima System.

PRODUCT DATA

Container size	4 litres
Form	Liquid
Application rate	Approx. 0.2 L/m ²
Density	1.198 kg / litre
Application temperature	5 °C to 30 °C
Colour	Oxide red

INTENDED USE

- To promote adhesion of Sealoflex Ultima Waterproof Coating on metal surfaces.

PRODUCT TESTING

BMI Sealoflex Ultima has been independently site and laboratory tested by the British Board of Agrément and awarded BBA certificate number 15/5229.



ADVANTAGES

- Forms a tough, non-chip film
- Good chemical and abrasion resistance
- Quick drying
- No dangerous fumes from solvents
- Used as a primer for all bare metal accessories, such as drip edge trims, etc.

SURFACE PREPARATION

Before applying Ultima Metal Etch Primer ensure that the surface is clean, dry and sound. Remove loose rust and mill scale by wire brush, abrasive disk or sandpaper. Treat with Sealoflex Ultima Rust X-2020 as required.

The surface temperature must be between 5° C and 3° C above the dew point. (Refer to the Dew Point Calculation Table in the Sealoflex Ultima Installation Manual).

Do not apply if rain is imminent.

APPLICATION INSTRUCTIONS

- 1 Remove the lid of the container and stir product with a mixing stick or a mechanical mixer at low speed.
- 2 Apply product to the substrate using a roller or a brush.
- 3 The minimum consumption is 0.2 litre / m²; this may increase depending on the texture of the surface.
- 4 Allow primer to dry thoroughly before applying Sealoflex Ultima Waterproof Coating.

Please note: Do not apply Sealoflex Ultima Metal Etch Primer over existing asphalt, bituminous coatings or bituminous aluminium coatings.

CLEANING

Clean tools in water immediately after use.

STORAGE

Store the product at temperatures between 5°C and 35°C. Where the product is exposed to temperatures below 5°C, ensure duration of exposure is no greater than 5 days. For optimum usage it is recommended to maintain the material above 15°C overnight prior to use. Materials should not be exposed to freezing conditions, as this will result in the products being unusable. Product stored at low temperatures prior to use will appear thicker in consistency and may take longer to cure. Do not expose to direct sunlight or cold winds. **Do not expose to rainfall.**

HEALTH & SAFETY

Information regarding transportation, handling, storage and disposal can be found on the Safety Data Sheet and on the label of the container. All recommendations and warnings must be observed.

TECHNICAL SERVICES

Specialist advice and design guidance on all matters relating to the Sealoflex Ultima System is freely available from our Technical Services Team.

BMI UK & Ireland

BMI House
2 Pitfield
Kiln Farm
Milton Keynes
MK11 3LW
+44 (0) 1908 015760

We are committed to continuously enhancing and improving our product range. We reserve the right to change our product specifications. We reserve the right to correct any typographical or clerical error or omission. For the latest information contact customer service.