

Sealoflex Ultima Standard Reinforcing Fabric

Sealoflex Ultima Standard Reinforcing Fabric is a heat set, stitch-bonded and non woven Polyester fabric. It is a component of the Sealoflex Ultima System.

PRODUCT DATA

Roll sizes	1.00 m x 100 m 0.30 m x 100 m 0.10 m x 100 m
Form	Solid
Weight	120 g/m ²
Thickness	0.49 mm
Tensile strength	Length: min. 18 kg Width: min. 6 kg
Elongation	Length: max. 50% Width: max. 90%
Colour	White

INTENDED USE

To be used in conjunction with Sealoflex Ultima Waterproof Coating.

PRODUCT TESTING

BMI Sealoflex Ultima has been independently site and laboratory tested by the British Board of Agrément and awarded BBA certificate number 15/5229.



STORAGE

Store under dry conditions in original packaging. Protect against mechanical deformation and dust.

Shelf life is 24 months from date of manufacture.

HEALTH & SAFETY

Information regarding transportation, handling, storage and disposal can be found on the Safety Data Sheet. All recommendations and warnings must be observed.

TECHNICAL SERVICES

Specialist advice and design guidance on all matters relating to the Sealoflex Ultima System is freely available from our Technical Services Team.

We are committed to continuously enhancing and improving our product range. We reserve the right to change our product specifications. We reserve the right to correct any typographical or clerical error or omission. For the latest information contact customer service.



BMI UK & Ireland

BMI House
2 Pitfield, Kiln Farm
Milton Keynes MK11 3LW
+44 (0) 1908 015760

bmigroup.com/uk