

# Sealoflex Ultima TPO Primer

Sealoflex Ultima TPO Primer is a single component, solvent-based, low viscosity primer. It is a component of the Sealoflex Ultima System.

## PRODUCT DATA

<b>Container size</b>	1 litre
<b>Form</b>	Liquid
<b>Consumption</b>	0.1 litres per m <sup>2</sup>
<b>Surface temperature limits</b>	Above 5° C and 35 °C (and 3° C above the dew point)
<b>Drying time</b>	15 minutes*
<b>Shelf life</b>	12 months**
<b>Colour</b>	Transparent

\* At 23 °C and 50% relative humidity.

\*\* If stored in original container between 5° C and 20° C.

## INTENDED USE

- To promote adhesion of Sealoflex Ultima Waterproof Coating onto TPO /FPO synthetic membranes.

**Please note:** An adhesion test is required for installations onto this type of membrane.

## PRODUCT TESTING

BMI Sealoflex Ultima has been independently site and laboratory tested by the British Board of Agrément and awarded BBA certificate number 15/5229.



## SURFACE PREPARATION

Before applying Sealoflex Ultima TPO Primer ensure that the surface is clean, dry and sound. The surface temperature must be between 5 °C and 35°C and 3° C above the dew point. (Refer to the Dew Point

Calculation Table in the Sealoflex Ultima Installation Manual).

**Do not apply if rain is imminent.**

## APPLICATION INSTRUCTIONS

- This solvent based primer does not require mixing.
- Apply product to the substrate using a roller or a brush.
- The minimum consumption is 0.1 litre / m<sup>2</sup>.
- Allow primer to dry thoroughly before applying Sealoflex Ultima Waterproof Coating.

**Please note:** Sealoflex Ultima Waterproof Coating must be applied to the primed surface within 48 hours of application. If left longer, the surface must be re-primed.

## CLEANING

Clean tools in solvent immediately after use.

## STORAGE

Store the product at temperatures between 5°C and 32°C. Store containers on a level surface. Do not expose to direct sunlight. Keep away from sources of ignition. Do not expose to rainfall.

## HEALTH & SAFETY

Information regarding transportation, handling, storage and disposal can be found on the Safety Data Sheet and on the label of the container. All recommendations and warnings must be observed.

## TECHNICAL SERVICES

Specialist advice and design guidance on all matters relating to the Sealoflex Ultima System is freely available from our Technical Services Team.

We are committed to continuously enhancing and improving our product range. We reserve the right to change our product specifications. We reserve the right to correct any typographical or clerical error or omission. For the latest information contact customer service.



## BMI UK & Ireland

BMI House  
2 Pitfield, Kiln Farm  
Milton Keynes MK11 3LW  
+44 (0) 1908 015760

[bmigroup.com/uk](http://bmigroup.com/uk)