

Sealoflex Ultima Wearcoat Clear

Sealoflex Ultima Wearcoat Clear is a single component, UV-resistant, protective coating. It is a component of the Sealoflex Ultima Anti-skid Walkway System.

PRODUCT DATA

| | |
|----------------------------------|--|
| Container size | 4 litre and 20 litre |
| Form | Liquid |
| Coverage rate | 0.3 kg/m ² |
| Surface temperature limit | Above 5° C (and 3° C above the dew point) |

CURING BEHAVIOUR

| | |
|--------------------------------------|-------------|
| Pot life / workability period | 60 minutes* |
| Rainproof | 20 minutes* |
| Walkable | 30 minutes* |
| Shelf life | 12 months** |
| Colour | Milky white |

* At 23 °C and 50% relative humidity.

** From date of manufacture in original unopened containers.

INTENDED USE

Sealoflex Ultima Wearcoat Clear forms part of the Sealoflex Ultima Anti-skid Walkway System and is used as a final encapsulation and UV protection layer above the embedded Sealoflex Ultima Quartz.

PRODUCT TESTING

BMI Sealoflex Ultima has been independently site and laboratory tested by the British Board of Agrément and awarded BBA certificate number 15/5229.



SURFACE PREPARATION

Before applying Ultima Wearcoat Clear ensure that there are no loose Quartz granules on the surface and that it is clean and dry. The surface temperature must be above 5° C and 3° C above the dew point. (Refer to the Dew Point Calculation Table in the Sealoflex Ultima Installation Manual). Do not apply if rain is imminent.

APPLICATION INSTRUCTIONS

- 1 Remove the lid of the container and stir product with a mixing stick or a mechanical mixer at low speed until it has reached an even consistency.
- 2 Apply product to the Quartz surface using a roller or a brush.
- 3 Coverage rate of 0.3 kg/m² applied in one coat.

Please note: Sealoflex Ultima Wearcoat Clear is milky white when applied. As it dries it becomes transparent, giving the surface a 'shiny' appearance. If the 'shine' is not visible apply a further coat, wait for it to dry and check the surface.

CLEANING

Clean tools in water immediately after use.

QUALITY ASSURANCE

Sealoflex Ultima Wearcoat Clear is supplied under a Quality Management System approved to EN ISO 9001: 2015 by TÜV NORD CERT GmbH.



STORAGE

Store the product at temperatures between 5°C and 35°C. Where the product is exposed to temperatures below 5°C, ensure duration of exposure is no greater than 5 days. For optimum usage it is recommended to maintain the material above 15°C overnight prior to use. Materials should not be exposed to freezing conditions, as this will result in the products being unusable. Product stored at low temperatures prior to use will appear thicker in consistency and may take longer to cure. Do not expose to direct sunlight or cold winds. Do not expose to rainfall.

TECHNICAL SERVICES

Specialist advice and design guidance on all matters relating to Sealoflex Ultima systems is freely available from our Technical Support Team.

BMI UK & Ireland

BMI House
2 Pitfield
Kiln Farm
Milton Keynes
MK11 3LW
+44 (0) 1908 015760

We are committed to continuously enhancing and improving our product range. We reserve the right to change our product specifications. We reserve the right to correct any typographical or clerical error or omission. For the latest information contact customer service.