

CI/SFB	September 2014		
993	(47)	Xh3	
Uniclass	JQ37: L7134: P4131		
Issue 01			

# Roofgard Terrace Grate

## Green Roof Systems



### Introduction

When installing a green roof system it is important to keep the green roof substrate away from outlets to keep the drainage free flowing. An Icopal Terrace Grate allows simple access to the outlet for cursory inspection and cleaning purposes. Icopal Terrace Grates are available in three heights and can be adjusted to suit the build-up height.

### Description

Icopal Terrace Grates are manufactured from stainless steel and comprise three sections; a base with a flange, a sleeve, and a grate. Three units are available and each unit is adjustable to provide a range of possible heights. Water run-off is provided by lateral slots at the bottom of the unit. The sleeve is positioned to the required height and fixed with blind rivets. The grate is perforated and is secured with two M6 steel mounting bolts.

### Intended Use

Icopal Terrace Grates are intended for use at outlet positions within extensive green roofs such as sedum, wildflower and biodiverse roof systems.

### Properties

Composition	Stainless Steel
Size	200 mm x 200 mm
Height Range	60 mm – 90 mm 90 mm – 120 mm 120 mm – 150 mm

### Technical Services

Specialist advice and design guidance on all matters relating to Icopal Green Roof Systems is freely available from our Technical Department at the address below.

### Availability

Item Code	Description	Size
3005274	Roofgard Terrace Grate	60 – 90 mm
3005275	Roofgard Terrace Grate	90 – 120 mm
3005276	Roofgard Terrace Grate	120 – 150 mm



NOTE: This information is given in good faith being based on the latest knowledge known to Icopal Limited. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume, based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.