

# Declaration of Performance

In accordance with Regulation (EU) N<sup>o</sup> 305/2011;

## 1. Unique identification code of the product-type

| Unique Identification Code | Product Name      | Nominal Dimensions |
|----------------------------|-------------------|--------------------|
| 3000187                    | Xtra-Load SA      | 19.05 m x 1.05 m   |
| 3100423                    | Xtra-Load Diamond | 19.05 m x 1.05 m   |
| 3100407                    | Xtra-Load GRM     | 19.05 m x 1.05 m   |

|    |  |   |
|----|--|---|
| 2. | Type, batch or serial number allowing identification of the construction product as required pursuant to Article 11 (4)                | See product label - Valid from 01.07.2013   |
| 3. | Intended use   | Plastic or rubber damp proof sheets intended for use as a damp-proof and tanking membranes.   |
| 4. | Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5)    | Icopal Limited<br>Barton Dock Road, Manchester, M32 0YL. United Kingdom   |
| 5. | Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) | Not relevant  |
| 6. | System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V         | System 2+   |
| 7. | In case of the declaration of performance concerning a Construction product covered by a harmonised standard                           | Notified factory production control certification body <b>No. 0836</b> performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) <b>0836- CPR - 13/F066</b> |
| 8. | In case of the declaration of performance concerning a Construction product for which a European Technical Assessment has been issued  | Not relevant  |

## 9. Declared Performance

| Essential Characteristic            | Performance | Tolerance | Units | Harmonised technical specification |
|-------------------------------------|-------------|-----------|-------|------------------------------------|
| Reaction to fire                    | Class F     | -         | -     | EN 13967:2012                      |
| Watertightness                      | Pass        | -         | -     |                                    |
| Resistance to Cold Bend             | ≤ -10       | -         | °C    |                                    |
| Dangerous Substances                | NPD         | -         | -     |                                    |
| Durability                          |             |           |       |                                    |
| Watertightness (against aging):     | Pass        | -         | -     |                                    |
| Watertightness (against chemicals): | Pass        | -         | -     |                                    |

*MD = Machine Direction. TD = Transverse Direction. NPD = No Performance Determined.*

Signed for and on behalf of the manufacturer by:

Neil Harrison  
Position: Technical Director  
Place: Manchester, UK  
Date: 06 May 2014



..... (signature)