

# Declaration of Performance



ETAG 005

13

ETA 03/ 0044

In accordance with Regulation (EU) N° 305/2011;

We the manufacturer:

**Icopal Ltd**  
**Barton Dock Road, Manchester, M32 0YL. United Kingdom**

Hereby declare the product(s) named below:

**Elastoflex Solvent Free Coating; Elastoflex Reinforcing Mat;**

Production location ref: S0008-02-101

Complies with the provisions concerning the attestation of conformity and product performance as described in **ETAG 005 - Guidelines for European Technical Approval of liquid applied waterproofing kits.**

**Description and Use:** ETAG 005, part 6: Liquid applied roof waterproofing kits on the basis of polyurethane; in-situ applied by spraying or spreading, with or without a supporting layer, an internal layer and/or a protection layer.

**System of assessment of verification of constancy of performance (AVCP):** System 3

The approval body Deutsches Institut für Bautechnik (DIBt) issued ETA-03/0044 on the basis of ETAG 005.

Determination of the product type on the basis of Initial Type Testing (ITT), type calculation, tabulated values or descriptive documentation of the product under system AVCP 3 was carried out by notified testing laboratory N°s. 1119, 0761, and 1378.

# Declaration of Performance

## TECHNICAL DATA

Characteristic	Value or statement	Harmonised Technical Specification
External fire performance	B <sub>ROOF</sub> (t1)	ETAG 005 (6-2004)  ETA 03/0044
Reaction to fire	Class E	
Statement on dangerous substances	None	
Resistance to plant roots	Resistance to root penetration	
Working life	W3	
Climatic Zones	M and S	
Imposed loads	P1 to P4	
Roof slope	S1 to S4	
Lowest surface temperature	TL4 (-30 °C)	
Highest surface temperature	TH4 (+90 °C)	

Signed for and on behalf of the manufacturer by:



Neil Harrison  
 Position: Technical Director  
 Place: Manchester, UK  
 Date: 18 June 2013