

Declaration of Performance

In accordance with Regulation (EU) N° 305/2011;

1. Unique identification code of the product-type

| Unique Identification Code | Product Name | Nominal Dimensions | Nominal Weight (kg·m ⁻²) |
|----------------------------|---------------------|--------------------|--------------------------------------|
| 3002776 | Monarflex Ultra 300 | 25 m x 2.0 m | 0.308 |
| 3002777 | Monarflex Ultra 300 | 25 m x 4.0 m | 0.308 |

| | | |
|----|--|---|
| 2. | Type, batch or serial number allowing identification of the construction product as required pursuant to Article 11 (4) | See product label - Valid from 01.07.2013 |
| 3. | Intended use | Plastic or rubber sheets intended for use as a damp-proof membrane on or beneath floors/ground slabs not subject to hydrostatic pressure. |
| 4. | Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5) | Icopal Limited Barton Dock Road, Manchester, M32 0YL, United Kingdom |
| 5. | Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) | Not relevant |
| 6. | System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V | System 2+ |
| 7. | In case of the declaration of performance concerning a Construction product covered by a harmonised standard | Notified factory production control certification body No. 1162 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 1162-CPD-0254 |
| 8. | In case of the declaration of performance concerning a Construction product for which a European Technical Assessment has been issued | Not relevant |


9. Declared Performance

| Essential Characteristic | Performance | Tolerance | Units | Harmonised technical specification | |
|-------------------------------------|----------------------|-----------|---------|------------------------------------|--|
| Reaction to fire | Class F | - | - | EN 13967 | |
| Watertightness | Pass | - | - | | |
| Tensile Strength | MD: >300 TD: >300 | - - | N/50 mm | | |
| Elongation | MD: >20 TD: >20 | - - | % | | |
| Resistance to Tearing | MD: >250 TD: >250 | - - | N | | |
| Equiv. air thickness | Sd = >250 | - | m | | |
| Joint Strength (tape) | >60 | - | N/50 mm | | |
| Resistance to Cold Bend | ≤ -20 | - | °C | | |
| Durability | | | | | |
| Watertightness (against aging): | Pass | - | - | | |
| Watertightness (against chemicals): | Pass | - | - | | |

MD = Machine Direction. TD = Transverse Direction.

Signed for and on behalf of the manufacturer by:

Neil Harrison
Position: Technical Director
Place: Manchester, UK
Date: 01 July 2013


 (signature)